

Card Printer Solutions



P430i Card Printer

Performance, Reliability, and Expandability in a Dual-sided Card Printer



Ideal for:

- » Employee ID cards
- » Student and faculty ID cards
- » Access control cards
- » Personalised membership and loyalty cards
- » Gift cards
- » Visitor ID cards
- » Government Licences

The Zebra P430*i* is part of the latest generation of Zebra's most popular card printer family, with tens of thousands of printers installed worldwide. Designed and built for demanding environments, the P430*i* delivers reliability and performance for high-volume card production. Expansion options for networking and card encoding give the P430*i* the flexibility to meet your specific requirements. Affordable and easy to use, the Zebra P430*i* is the new leader in dual-sided performance card printers.

Innovative and Easy-to-Use

- » Easy plug and play USB or USB with Ethernet interface simplifies configuration
- » Printhead bracket opens wide for easy ribbon access
- » 16 character LCD screen for printer status and error reporting messages
- » Translucent card cover allows you to see when supplies are running low, and blank cards can be added while printing
- Reject bin holds cards that fail to encode correctly

Encoding and Network Connectivity Expansion Options

- » 3 track magnetic stripe encoding (HiCo/LoCo)
- Contact and contactless smart card encoding capabilities
- » Built-in 10/100 Ethernet for printer networking simplifies device management and eliminates the need for third party external device.

Reliable and Flexible

ST P430

- » Print dual-sided or single-sided
- » Revolutionary angled card feeder design means fewer rejected cards*
- » Self-aligning printhead design for consistently uniform print quality

High Performance

- » Vibrant, true-to-life colours
- » High volume card throughput
- » Large capacity card feeder available

i Series* Functionality

- » Automatic colour optimisation and driver configuration
- » Enhanced ribbon formulation for optimal colour output
- » Ribbon image counter and ribbon low notification

*Patent pending

P430i

Card Printer Product Specifications



General Specifications	Ribbon Specifications*
» 16-character LCD display	» i Series [™] Printers require the use of i Series ribbons for full colour printing
» Windows [®] drivers for 2000 and XP	» YMCKOK: 170 cards/roll
» Bi-directional driver communication	» YMCKO: 200 & 330 cards/roll » 1/2 Panel YMC Full KO: 450 cards/roll
» Two year printer warranty	
» Two year (unlimited passes) printhead warranty	» KdO: 500 cards/roll
	» KrO: 500 cards/roll
Printing	» Overlay varnishes: Clear and Hologram: 350 cards/roll
» Colour dye sublimation or monochrome thermal transfer printing	 Monochrome: 1500 (Black) & 1000 cards/roll
» 102 cards per hour full colour dual-sided (YMCKOK)	» Monochrome colours: black, red, blue, green, silver, gold, white and
» 130 cards per hour full colour single-sided (YMCKO)	scratch-off grey
» 300 dpi (11.8 dots/mm) print resolution	*for optimum printer performance use Genuine Zebra Supplies
	Mechanical
Bar Codes	Width: 26 in (660 mm)
» Code 39, Code 128 B & C with & without check digit	» Depth: 9.4 in (239 mm)
» 2 of 5 & 2 of 5 Interleaved	» Height: 10.1 in (256 mm)
» UPC-A, EAN 8 & EAN 13	» Weight: 20 lbs (9.1 kg)
» PDF-417 2D bar code and other symbologies can be printed via	
Windows drivers	Electrical
	» 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
Card Specifications	» 4MB image memory standard
» Types: PVC, PVC Composite, Adhesive backed	» FCC Class A, CE, UL, CUL, and CCC approved
» Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)	
» Magnetic Stripe-ISO 7811	Environmental
» Smart Card contact and contactless	» Operating Temperature: 60°F to 86°F (15°C to 30°C)
» Card thickness: 10 mil (.25mm) to 60 mil (1.524mm) (+/- 10%)	» Operating Humidity: 20% to 65% non-condensing
» Card feeder capacity: 100 cards (30 mil) or 220 cards (30 mil)	» Storage Temperature: 23°F to 158°F (-5°C to 70°C)
» Card output hopper capacity: 100 cards (30 mil)	» Storage Humidity: 20% to 70% non-condensing
	» Ventilation: Free air
Communications Interface	– Options
» USB 1.1 (USB 2.0 compatible) cable included	» Built-in 10/100 Mbps Ethernet
» Optional Built-in 10/100 Mbps Ethernet	 » Smart card contact-ISO 7816 encoder (30 mil cards only)
	 » Smart card MIFARE*/DESFire and HID iClass* encoder (30 mil cards only)
	 » Magnetic encoder (30 mil cards only) 3 track HiCo/LoCo
	 » High capacity feeder (220 cards)
	» Cleaning supplies
Designed for ROHS Software drivers for the Zebra P430i Card Printer have been tested to ensure that they meet Microsoft* standards	Genuine Zebra Supplies
for Windows [®] compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks	» Your choice of card printer supplies is critical. It is a primary factor affect-
Windows bg/ are trademarks, or registered trademarks Windows 2000 of Microsoft Corporation in the United States and/or other	ing the reliability and consistency of printing. Genuine Zebra Supplies mee
countries.	stringent quality standards and are tested for optimum performance with

www.zebracard.com



An ISO 9001 registered company ©2005 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied Part No. P430i-05/06 by the use thereof.

North America

Zebra Technologies Corporation Card Printer Solutions 1001 Flynn Road Camarillo, CA 93012-8706

USA Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra card printers.

Zebra Technologies Corporation

Card Printer Solutions The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765 e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation **Card Printer Solutions** 16 New Industrial Road #05-03 Hudson TechnoCentre Singapore 536204

Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

stringent quality standards and are tested for optimum performance with

Latin America

Zebra Technologies Corporation **Card Printer Solutions** 9800 NW 41st Street, Suite 220 Doral, FL 33178 USA Telephone: +1 305 558 3100 Fax: +1 305 558 8485 e-mail: latinsales@zebra.com